



MEASURED FOR SUCCESS

POWER LIFT SLH	3500	4600*	5500*
Lifting capacity (kg)	3500	4600	5500
Lifting/lowering time approx. (sec)	35/28	35/28	40/30
Lifting height (mm)	1940	1990	2015
Lowest lifting point (mm) Version DT	95-155	-	-
Version MINI-MAX	75-185	-	-
Version SC	84-144	-	-
Version Otto*	115-190	-	-
Version Otto MM*	90-185	-	-
Version Otto VT*	90-202	-	-
Version Universal	-	115-190	130-205
Version DG	-	-	140-215
Total height (mm)	4054/4595	4054/4600	4054/4600/4950
Recommended total width (mm)	3230/3330	3370	3570/3670
Column distance (mm)	2676/2776	2786	2779-2879
Arm-extraction long (mm) Version DT	940-1495	-	-
Version MINI-MAX	1000-1480	-	-
Version SC	840-1380	-	-
Version Otto*	995-1823	-	-
Version Otto MM*	930-1850	-	-
Version Otto VT*	995-1825	-	-
Version Universal	-	930-1850	860-1850
Version DG	-	-	0-1823
Arm-extraction short (mm) Version DT	570-1170	-	-
Version MINI-MAX	600-980	-	-
Version SC	590-865	-	-
Version Otto*	570-1160	-	-
Version Otto MM*	590-1160	-	-
Version Otto VT*	495-870	-	-
Version Universal	-	590-1160	860-1850
Version DG	-	-	0-1823
Power supply (V/Hz/A)	400/50/16	400/50/16	400/50/16

*All technical data preliminary, lifts currently in development. Final details after product release.

ACCESSORIES



Height adapter 44 mm



Height adapter 155-245 mm




U-form adapter 150-233 mm

More accessories available

HYDRAULIC 2-POST LIFT

POWER LIFT SLH

ONE LIFT. ENDLESS POSSIBILITIES.



THE NEW GENERATION OF SMART LIFTS

- ✓ Best in market pick-up area and arm range for full flexibility and EV compatibility
- ✓ Space-saving design based on SMART LIFT Series. Up to 10% more space compared to other manufacturers
- ✓ Up to 50% less installation time due to pre-assembly and the patent pending Quick-traverse
- ✓ Fine adjustable pick-up pads with additional instant-adjust (patent pending)
- ✓ CE-Stop preinstalled in all versions, no hang-in foot protectors needed

3500 KG | 4600 KG | 5500 KG




HYDRAULIC 2-POST LIFT

POWER LIFT SLH

Space saving, flexible and fully customizable

Fast lifting and lowering times, mechanical safety ratchets, mechanical synchronization, high productivity, intelligent features and life cycles up to 30 years: It is not without reason that Nussbaum lifts are among the world's leading equipment in automotive workshops. The POWER LIFT SLH is the perfect combination of robustness, premium hydraulics and mechanical safety while having industry leading pick-up possibilities. German quality at the service of your workshop.

5500 KG



DG - Arm
Double jointed for the biggest pick-up range in the industry

Universal - Arm
the perfect partner for the transporter workshop

4600 KG



Universal - Arm
the Allrounder for cars and transporters

OTTO 3500 KG



Otto - Arm
perfect combination of double jointed and double telescopic arms

Otto MM - Arm
Additional comfort with Mini-Max Arms

Otto VT - Arm
High end, quick adjustable pick-up pads for very narrow spots especially for battery disassembly

3500 KG



DT - Arm
short arm has 3 stages

MM - Arm
Ideal for deep drawn side skirt or off-road vehicles

SC - Arm
Extremely flat construction

EV - Arm
more flexibility for Electric Vehicles

ACCESSORIES



Wheel-fork adapter for SLH 5500


Mini-Max adapter for SLH 5500, Capacity 4200 kg



Full range of plug in adapters available
The perfect match for every gasoline, hybrid or fully electric vehicle

VARIABLE HEIGHT & WIDTH

Minimal height of only 4054 mm, up to 4950 mm with optional column extension



POWER LIFT SLH: different versions built to your needs

All versions available with full range of arms and two different height extensions

Mechanical

Air cooled power unit with manual latch control

Advanced

Air cooled power unit with electric latch control

Premium

Oil submerged power unit with Nussbaum Commander for precise lowering and automatic latch control. Specifically designed for battery disassembly

Options

Two different height extensions, cylinder covers and E-set available for all versions

Thoughtful design

- ✓ No floor connections
- ✓ Manual or electric latch control available
- ✓ Parking position for comfortable working
- ✓ Two height extensions available
- ✓ Optional cylinder Cover available
- ✓ Door protection on columns
- ✓ Compressed air and power connection (220 V) integrated in column available
- ✓ Oil submerged motor available: Durable and quiet, constant oil viscosity and therefore constant running speed - even at cold temperatures

Precise control

- ✓ Smooth, sensitive lowering in the mm range thanks to Optional NUSSBAUM Commander
- ✓ No lifting before lowering necessary with optional automatic latch control